

Schedule 5S
Stainless steel alloys only

Nominal pipe size	Outside diameter (O.D.)	Center to face (A)	Schedule 5S		
			Inside diameter	Wall thickness (T)	Approx. weight **
1/2	.840	1-1/2	.710	.065	.12
3/4	1.050	1-1/2	.920	.065	.13
1	1.315	1-1/2	1.185	.065	.19
1-1/4	1.660	1-7/8	1.530	.065	.31
1-1/2	1.900	2-1/4	1.770	.065	.38
2	2.375	3	2.245	.065	.64
2-1/2	2.875	3-3/4	2.709	.083	1.50
3	3.500	4-1/2	3.334	.083	2.00
3-1/2	4.000	5-1/4	3.834	.083	2.62
4	4.500	6	4.334	.083	3.31
5	5.563	7-1/2	5.345	.109	6.50
6	6.625	9	6.407	.109	10.00
8	8.625	12	8.407	.109	17.30
10	10.750	15	10.482	.134	32.00
12	12.750	18	12.438	.156	51.00
14	14.000	21	13.688	.156	68.00
16	16.000	24	15.670	.165	100.00
18	18.000	27	17.670	.165	125.00
20	20.000	30	19.624	.188	165.00
24	24.000	36	23.564	.218	280.00

Schedule 10S
Stainless steel, Nickel & Aluminum alloys

Nominal pipe size	Outside diameter (O.D.)	Center to face (A)	Schedule 10S		
			Inside diameter	Wall thickness (T)	Approx. weight **
1/2	.840	1-1/2	.674	.083	.14
3/4	1.050	1-1/2	.884	.083	.15
1	1.315	1-1/2	1.097	.109	.30
1-1/4	1.660	1-7/8	1.442	.109	.50
1-1/2	1.900	2-1/4	1.682	.109	.69
2	2.375	3	2.157	.109	1.13
2-1/2	2.875	3-3/4	2.635	.120	1.88
3	3.500	4-1/2	3.260	.120	2.69
3-1/2	4.000	5-1/4	3.760	.120	3.75
4	4.500	6	4.260	.120	4.75
5	5.563	7-1/2	5.295	.134	8.00
6	6.625	9	6.357	.134	12.00
8	8.625	12	8.329	.148	23.50
10	10.750	15	10.420	.165	43.00
12	12.750	18	12.390	.180	60.00
14	14.000	21	13.624	.188	80.00
16	16.000	24	15.624	.188	105.00
18	18.000	27	17.624	.188	132.00
20	20.000	30	19.564	.218	220.00
24	24.000	36	23.500	.250	310.00

Schedule 40S
Stainless steel, Nickel & Aluminum alloys

Nominal pipe size	Outside diameter (O.D.)	Center to face (A)	Schedule 40S		
			Inside diameter	Wall thickness (T)	Approx. weight **
1/2	.840	1-1/2	.622	.109	.18
3/4	1.050	1-1/2	.824	.113	.19
1	1.315	1-1/2	1.049	.133	.35
1-1/4	1.660	1-7/8	1.380	.140	.56
1-1/2	1.900	2-1/4	1.610	.145	.88
2	2.375	3	2.067	.154	1.56
2-1/2	2.875	3-3/4	2.469	.203	3.00
3	3.500	4-1/2	3.068	.216	4.81
3-1/2	4.000	5-1/4	3.548	.226	6.25
4	4.500	6	4.026	.237	9.19
5	5.563	7-1/2	5.047	.258	15.13
6	6.625	9	6.065	.280	24.00
8	8.625	12	7.981	.322	47.50
10	10.750	15	10.020	.365	85.00
12	12.750	18	12.000	.375	131.00
14	14.000	21	13.250	.375	155.00
16	16.000	24	15.250	.375	202.00
18	18.000	27	17.250	.375	269.00
20	20.000	30	19.250	.375	330.00
24	24.000	36	23.250	.375	464.00

Schedule 80S
Stainless steel, Nickel & Aluminum alloys

Nominal pipe size	Outside diameter (O.D.)	Center to face (A)	Schedule 80S		
			Inside Diameter	Wall thickness (T)	Approx. weight **
1/2	.840	1-1/2	.546	.147	.23
3/4	1.050	1-1/2	.742	.154	.25
1	1.315	1-1/2	.957	.179	.48
1-1/4	1.660	1-7/8	1.278	.191	.88
1-1/2	1.900	2-1/4	1.500	.200	1.13
2	2.375	3	1.939	.218	2.00
2-1/2	2.875	3-3/4	2.323	.276	4.00
3	3.500	4-1/2	2.900	.300	6.56
3-1/2	4.000	5-1/4	3.364	.318	8.80
4	4.500	6	3.826	.337	13.63
5	5.563	7-1/2	4.813	.375	21.13
6	6.625	9	5.761	.432	36.00
8	8.625	12	7.625	.500	73.00
10	10.750	15	9.750	.500	114.00
12	12.750	18	11.750	.500	175.00
14	14.000	21	13.000	.500	206.00
16	16.000	24	15.000	.500	269.00
18	18.000	27	17.000	.500	350.00
20	20.000	30	19.000	.500	439.00
24	24.000	36	23.000	.500	617.00

Schedule 160
Stainless steel alloys only

Nominal pipe size	Outside diameter (O.D.)	Center to face (A)	Schedule 160		
			Inside Diameter	Wall thickness (T)	Approx. weight **
1/2	.840	1-1/2	.464	.188	.29
3/4	1.050	1-1/2	.612	.219	.35
1	1.315	1-1/2	.815	.250	.67
1-1/4	1.660	1-7/8	1.160	.250	1.15
1-1/2	1.900	2-1/4	1.338	.281	1.59
2	2.375	3	1.689	.343	3.14
2-1/2	2.875	3-3/4	2.125	.375	5.44
3	3.500	4-1/2	2.624	.438	9.58
3-1/2	4.000	5-1/4	-----	-----	-----
4	4.500	6	3.438	.531	21.53
5	5.563	7-1/2	4.313	.625	35.29
6	6.625	9	5.187	.719	59.76
8	8.625	12	6.813	.906	132.00
10	10.750	15	8.500	1.125	256.00
12	12.750	18	10.126	1.312	458.00
14	14.000	21	11.188	1.406	-----
16	16.000	24	12.812	1.594	-----
18	18.000	27	14.438	1.781	-----
20	20.000	30	16.062	1.969	-----
24	24.000	36	19.312	2.344	-----

Schedule XX Strong Wall
Stainless steel alloys only

Nominal pipe size	Outside diameter (O.D.)	Center to face (A)	XX Strong Wall		
			Inside Diameter	Wall thickness (T)	Approx. weight **
1/2	.840	1-1/2	.252	.294	.46
3/4	1.050	1-1/2	.434	.308	.50
1	1.315	1-1/2	.599	.358	.96
1-1/4	1.660	1-7/8	.896	.382	1.76
1-1/2	1.900	2-1/4	1.100	.400	2.26
2	2.375	3	1.503	.436	4.00
2-1/2	2.875	3-3/4	1.771	.552	8.00
3	3.500	4-1/2	2.300	.600	13.12
3-1/2	4.000	5-1/4	2.728	.636	17.60
4	4.500	6	3.152	.674	27.26
5	5.563	7-1/2	4.063	.750	42.26
6	6.625	9	4.897	.864	72.00
8	8.625	12	6.875	.875	127.00